

RoomTracker VC Tracking Camera



AMC-E200TV2




The camera adopts the most advanced tracking technology, it can detect meeting participants non-stop and then automatically frame all the participants.

With its stability, easy-to-use and excellent performance, it is widely used in video conferencing rooms, and huddle rooms etc.

Features


- Advanced tracking technology. Getting perfect shot automatically with suitable P/T degree and zoom times, as per the attendee number and position;
- The distance between attendees and camera not more than 8 meters;
- Integrated wide-angle full-view camera;
- Max 1080P60 output;
- Support SDI, DVI-D, RJ45 and USB 2.0 outputs;
- H.264 video compression;
- IR remote and RS-232/RS-485 control;
- User-friendly interface and easy setup.

Dimensions



- 1 Audio
- 2 TF Card
- 3 Ethernet
- 4 DVI-D
- 5 3G-SDI
- 6 RS-232/RS-485
- 7 USB2.0
- 8 DC12V

Accessories



Wall Bracket

Technical Data

Model	AMC-E200TV2
Tracking Camera	
Image Sensor	1/2.8" CMOS, 2.14MP
Focal Length	f=3.9mm - 46.8mm
Iris	F1.6 - F2.8
Optical Zoom	12X
Digital Zoom	12X
FOV	Horizontal 72.5° - 6.3°
Focus	Auto, Manual, PTZ Trigger, One Push Trigger
Exposure Control	Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority
Shutter Speed	1/1 ~ 1/10,000s
Gain	Auto, Manual
White Balance	Auto, Indoor, Outdoor, One Push, Manual, Auto Tracking
SN Ratio	≥50dB
Full View Camera	
Image Sensor	1/2.8" CMOS, 2.14MP
Focal	2.4mm
Lens	Manual Fixed Focus
Exposure Control	Auto
White Balance	Auto
FOV	Horizontal: 86°, Vertical: 52°
PTZ	
Pan	-170° ~ +170°, 0.1° ~ 120°/S
Tilt	-30° ~ +90°, 0.1° ~ 90°/S
Preset Number	256
Control Interface	RS-232, RS-485, USB2.0
Protocol	PELCO-D, VISCA, UVC1.1
HD Video	
Video Output	3G-SDI, DVI-D, USB2.0
Video Format	1080P60, 1080P50, 1080P30, 1080P25, 1080I60, 1080I50, 720P60, 720P50
Network	
Network Interface	100M RJ45
Max Image Size	1920×1080@60fps
Image Compression	H.264/H.265
Audio Compression	AAC
Protocols	ONVIF, RTSP, RTMP, HTTP, TCP, UDP
Dual Stream	Support
General	
Power Supply	DC12V
Power Consumption	<15W
Working Temperature	0°C ~ +40°C
Storage Temperature	-20°C ~ +60°C
Dimensions (L×W×H)	243mm×145mm×163mm