

## 1080 P30 HD USB Camera

## iSmart Video



AMC-M1001V3

AMC-M series HD USB PTZ camera supports 1080P30 video resolution with vivid video effect, and brings excellent conference experience.



### 1080P30 HD Video



- Latest CMOS sensor, with 1080P30 video resolution;
- 10X optical HD lens, FOV up to 62°;
- Advanced 2D/3D noise reduction with excellent noise control performance.

### USB2.0 + Compact Design


- USB2.0 interface with standard UVC protocol, H.264/H.265/MJPEG encoding;
- Compact remote for easy use;
- Low power consumption, not more than 5W;
- Hidden interfaces for easy cabling.



## Dimensions



## Accessories (Optional)



Wall Bracket

### Contact Us

-  86-571-88842693
-  86-571-88842692
-  sales@ismart-video.com
-  www.ismart-video.com
-  4F. Bldg. 4, 16# Xiyuan Yi Road, Hangzhou, 310030, China



## Technical Data

Model	AMC-M1001V3
Image Sensor	1/2.8" CMOS, 2.16MP
Video Output Format	Max 1080P30fps
Lens	10X, f=5.15-47.38mm, F2.38
Field Of View	62.2°-7.08°
Focus System	Auto, Manual, PTZ Trigger
Min. Illumination	0.5Lux (color), 0.1Lux (B/W)
Shutter Speed	1/60s to 1/10,000s
Gain	Auto, Manual
White Balance	Auto, Manual, One Push Trigger, Auto Tracking
Exposure Control	Auto, Manual, Shutter Priority, Brightness Priority
SNR	≥50dB
DNR	2D/3D
BLC	Support

### PTZ

Pan Angle	-90°~+90°
Tilt Angle	-30°~+90°
Pan Speed	15°/S
Tilt Speed	10°/S
Preset Number	3 (when using remote control)

### Interface

Network Interface	1×10/100 RJ-45 (reserved)
Audio Input	1Line IN (reserved)
USB Interface	USB2.0
IR Remote Control	Support

### USB

Resolution	Max 1080@30fps
Image Compression	H264/H265/MJPEG
UVC Protocol	UVC 1.0
UVC PTZ Control	Support

### General

Power	DC12V
Power Consumption	<5W
Operating Temperature	0°C ~ +40°C
Storage Temperature	-20°C ~ +60°C
Relative Humidity	10% ~ 90%
Dimensions (W×D×H)	163mm×101mm×114mm (W×D×H)
Weight	0.6kg
Color	Black