

4K UHD Lecturer Tracking Camera

iSmart Video



LTC6-G500
LTC6-G500S(SDI)
LTC6-G500H(HD-BaseT)

LTC6-G500 is a 4K UHD tracking camera, its fast autofocus lens combined with smart algorithm can efficiently locate the tracked object, quickly focus, output HD pictures, to improve learning efficiency.

4K UHD, 12X Zoom

- 1/2.8" 4K CMOS, 8.46 MP;
- 4K ultra HD lens, 12x optical zoom, up to 81° FOV;



Smart Algorithm, High Precision PTZ




- Built in the industry-leading AI image algorithm for human body detection and lock tracking, which can realize a wide range of automatic detection and continuous tracking;
- Fast, accurate and smooth tracking;
- High precision, smooth rotation, quiet PTZ;

Rich Interfaces, High Compatibility

- H.264/H.265 video compression, up to 4KP60 video output, and support optional POE;
- HDMI2.0 video output, up to 4KP60 video output;
- Optional 3G-SDI or HD-BaseT video output;
- Support RS-232 IN/RS-232 OUT control interface and VISCA protocol;
- 1 channel LINE IN.



Dimensions



- | | |
|--------------------|-------------|
| ① 3G-SDI(Optional) | ⑥ REF |
| ② DIP Switch | ⑦ LINE IN |
| ③ Ethernet | ⑧ RS-232IN |
| ④ HDMI | ⑨ RS-232OUT |
| ⑤ USB2.0 | ⑩ DC12V |

Contact Us

- ☎ 86-571-88842693
- 🏢 86-571-88842692
- ✉ sales@ismart-video.com
- 🌐 www.ismart-video.com
- 📍 4F. Bldg. 4, 16# Xiyuan Yi Road, Hangzhou, 310030, China

Technical Data

Model	LTC6-G500(S/B)
Image Sensor	1/2.8"CMOS, 8.46MP
Lens	12X; f=3.4mm~40.3mm; F1.8 (Wide)~3.6 (Tele)
Field Of View	81°~ 7.6°
Focus	Auto/Manual
White Balance	Auto/Manual
Exposure Control	Auto/Manual
S/N	≥50dB
DNR	2D/3D
BLC	Support
PTZ	
Pan Angle	-130° ~ +130°; 0.2° ~ 80°/s
Tilt Angle	-30° ~ +90°; 0.2° ~ 60°/s
Image Flip	Support
Preset Number	64
Interface	
HDMI	1 channel HDMI 2.0; Support 4KP60/P50/P30/P25, 1080P60/P50/P30/P25, 1080I60/I50, 720P60/P50
Network	RJ45 (10M/100M), optional POE; 1.Support 4KP30/P25, 1080P30/P25, 720P30/P25, 360P30/P25 2.Image compression H.264/H.265
USB	1 channel USB2.0; 1.Support UVC 1.1 2.Image compression H.264/MJPEG; support 4KP30/P25, 1080P30/P25, 720P30/P25, 360P30/P25
3G-SDI (Optional)	1 channel 3G-SDI; support 1080P60/P50/P30/P25, 1080I60/I50, 720P60/P50
HD-BaseT (Optional)	1 channel HD- BaseT(optional); support 4KP30/P25, 1080P60/P50/P30/P25, 1080I60/I50, 720P60/P50
Audio Input	1 channel LINE IN, 3.5mm audio interface
Control Interface	1 channel RS-232 IN, 1 channel RS-232 OUT
DIP Switch	Rotating DIP switch to set video format
Power	DC12V
General	
Control Protocol	VISCA
Power Consumption	<18W
Operating Environment	Temperature: 0 ~ 40°C, Relative Humidity: 10%RH ~ 90 %RH
Storage Environment	Temperature: -20°C ~ +60°C, Relative Humidity: 10%RH ~ 95 %RH
Dimensions	245mm×146mm×164mm (W*D*H)
Weight	<2kg
Color	Grey