


# 4K PTZ Camera

## AMC-G303



- 1 USB 3.0
- 2 LINE IN
- 3 LAN
- 4 DC 12V

## Features

- 1/2.8" CMOS, 8.46MP;
- 3x optical zoom, up to horizontal 81°FOV;
- 6x lossless zoom at 1080P30 resolution;
- USB 3.0 support 4K video output;
- Support standard UVC/UAC protocol;
- Ethernet support H.265/H.264 video compression, up to 4K video output;
- Ethernet and USB 3.0 outputs;
- Dual stream.

## Technical Data

### Camera

**Image Sensor**

1/2.8" CMOS, 8.46MP

**Optical Zoom**

3x optical zoom

**Focal Length**

f=3.3mm ~ 9.7mm

**Iris**

F2 ~ F3.7

**HFOV**

81.4° ~ 31.3°

**Digital Zoom**

5x

**Focus System**

Auto, Manual, PTZ Trigger, One Push Trigger

**Shutter speed**

1/50 ~ 1/10,000s

**AGC**

Auto, Manual

**White Balance**

Auto, Manual, Auto Tracking, One Push, Static Color Temperature

**BLC**

Support

**Wide Dynamic**

Support

**Exposure**

Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority

**SNR**

≥50dB

### PTZ

**Pan**

-170°~+170°; 0.1°~120°/s

**Tilt**

-30°~+90°; 0.1° ~ 90°/s

**Image Filp**

Support

**Preset Number**

256

### General

**Power**

DC12V; <12W

**Operating Temperature**

0°C ~ +40°C

**Storage Temperature**

-20°C ~ +60°C

**Dimensions (L\*W\*H)**

176mm × 137mm × 171mm

**Weight**

≤1.2kg

### Interface

**Network**

1 × RJ45:1×10M/100M

1. Image Compression:

H.264/H.265:

1080P60/P50/P30/P25,

720P60/P50/P30/P25

2.Protocol:

ONVIF/RTSP/RTMP/TCP/UDP

/SRT/RTMPS/GB28181

3. Audio Compression:

AAC/G.711

**USB 3.0**

1. Support UVC1.1

2. UVC Support:

H.264/H.265/MJPEG:

4KP20, 1080P30/P25,

720P30/P25

YUY2/NV12: 1080P30/P25,

720P30/P25

3. UAC Audio Format PCM

**Audio**

1 × LINE IN, 3.5mm