


1080P60 PTZ Camera

AMC-G312U3/G310U3



- 1 USB3.0
- 2 HDMI
- 3 LINE IN
- 4 LAN
- 5 RS-232 IN
- 6 RS-232 OUT/RS-485
- 7 DC 12V

Features

- 1/2.8" CMOS, 2.14MP;
- 12x/10x optical zoom, up to 1080P60 video output;
- HDMI, Ethernet and USB 3.0 outputs;
- Support standard UVC/UAC protocols;
- USB support YUY2 uncompressed video formats, up to 1080P30 resolution;
- RS-232 In & RS-232 Out, support daisy chain;
- H.265/H.264 video compression, up to 1080P60 video output;
- Dual stream.

Technical Data

Camera

AMC-G312U3

Image Sensor
1/2.8" CMOS, 2.14 MP

Iris
F1.6 ~ F2.8

Focal Length
f=4.14mm ~ 47.08mm

HFOV
72.5° ~ 6.3°

Optical Zoom
12x

AMC-G310U3

Image Sensor
1/2.8" CMOS, 2.14 MP

Iris
F1.6 ~ F3.0

Focal Length
4.3mm ~ 43mm

HFOV
71° ~ 8°

Optical Zoom
10x

PTZ

Pan
-170° ~ +170°; 0.1° ~ 120°/s

Tilt
-30° ~ +90°; 0.1° ~ 90°/s

Preset Number
256

General

Power
DC12V; <15W

Control Protocol
VISCA (Support daisy chain) / PELCO-P / PELCO-D

Operating Temperature
0°C ~ +40°C

Storage Temperature
-20°C ~ +60°C

Dimensions (L×W×H)
176mm × 137mm × 171mm

Weight
≤1.2kg

Other Camera Data

Digital Zoom

16x

Focusing System

Auto, Manual, PTZ Trigger, One Push Trigger

Shutter speed

1/50 ~ 1/10,000s

AGC

Auto, Manual

White Balance

Auto, One Push, Manual, ATW, Static Color Temperature

BLC

Support

Wide Dynamic

Support

Exposure

Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority

SNR

≥50dB

Interface

HDMI

1080P60/P50/P30/P25,720P60/P50/P30/P25,480P60/P50/30/25

Network

1×RJ45:1×10M/100M

1. Video Output Format: Max 1080P60;

2. Image Compression: H.264/H.265

3.Protocol:ONVIF/RTSP/RTMP /TCP/UDP/SRT;

4. Audio Compression: AAC

5. Support multiple stream

USB 3.0

1. Support UVC1.1

2. UVC Support:

H.264/H.265/MJPEG: 1080P60/P50/P30/P25, 720P60/P50/P30/P25, 480P60/P50/P30/P25, 360P60/P50/P30/P25

YUY2/NV12: 1080P30/P25, 720P30/P25, 480P30/P25, 360P30/P25

3. UAC Audio Format PCM

Audio

1×LINE IN, 3.5mm

Control Interface

1×RS-232 In

1×RS-232 Out/RS-485