

4KP60 PTZ Camera


AMC-G530/G520/G500



4KP60



30x/20x/12x
Optical Zoom



- | | |
|--------------|--------------|
| 1 DIP Switch | 6 LINE IN |
| 2 LAN | 7 RS-232 IN |
| 3 HDMI 2.0 | 8 RS-232 OUT |
| 4 USB 2.0 | 9 DC 12V |
| 5 Reserved | |

Features

- 1/2.8" 4K CMOS, 8.46MP;
- 4K super resolution lens, max 30x optical zoom, max HFOV: 81°, max support 4KP60;
- Support HDMI, USB, Ethernet interface, support POE;
- High precision, smooth rotation, quiet PTZ;
- Supports multiple control protocol and interface, support daisy chain.

Technical Data

Camera

AMC-G530	AMC-G520	AMC-G500
Focal f=5.2mm ~ 155.8mm	Focal f=5.2 ~ 104mm	Focal f=3.4mm ~ 40.3mm
Iris F1.8 ~ F5.2	Iris F1.8 ~ 3.5	Iris F1.8 ~ F3.6
Optical Zoom 30x	Optical Zoom 20x	Optical Zoom 12x
HFOV 59° ~ 1.2°	HFOV 59°~2.9°	HFOV 81° ~ 7.6°

Other Camera Data

Image Sensor
1/2.8" CMOS, 8.46MP

Image
Auto Focus, Auto Exposure, Auto White Balance

SNR
≥55dB

BLC/WDR
Support

PTZ

Pan
-130°~+130°, 0.1°~87°/s

Tilt
-30°~+90°, 0.1°~67°/s

Preset Number
64

Menu
Support

General

Control Protocol
VISCA

Power
DC12V; <18W

Dimensions (L×W×H)
245mm×146mm×164mm

Operating Temperature
0°C ~ +40°C

Storage Temperature
-20°C ~ +60°C

Weight
<2kg

Interface

HDMI 2.0
4KP60/P50/P30/P25,
1080P60/P50/P30/P25,
1080I60/I50, 720P60/P50

USB 2.0
Support UVC 1.5
MJPEG/H.264, 4KP30/P25,
1080P30/P25, 720P30/P25,
360P30/P25

Network Interface
1×10M/100M/1000M RJ45 POE
Max 4KP60

Audio Compression
AAC

Audio Input
1×LINE IN, 3.5mm

Network Protocol
RTSP/ONVIF
/RTMP/HTTP/TCP/UDP/ RTP

Dual Stream
Main/Sub