


1080P60 PTZ Camera

AMC-E220NV4/E200NV4



- | | |
|-----------|---------------|
| ① HDMI | ⑤ RS-232IN/IR |
| ② USB2.0 | ⑥ RS-232OUT |
| ③ LINE IN | ⑦ DC 12V |
| ④ LAN | |

Features

- Adopts 1/2.8-inch CMOS sensor, 2.14 million pixels;
- HDMI/USB high-definition video output;
- Precise transmission system, accurate positioning, smooth operation;
- Multiple protocols and multiple control interfaces, daisy chain networking;
- Equipped with multi-functional IR remote control;
- Intelligent exposure effectively solves the influence of projectors, TVs, and other devices on shooting subjects;
- Three installation methods: desktop, wall-mounted, and ceiling mounted.

Technical Data

Camera

AMC-E220NV4

Image Sensor

1/2.8" CMOS, 2.14 MP

Optical Zoom

20x

Iris

F1.6~3.5

Focal Length

f=4.7~94.0mm

HFOV

59.5°~2.9°

AMC-E200NV4

Image Sensor

1/2.8" CMOS, 2.14 MP

Optical Zoom

12x

Iris

F1.6~F2.8

Focal Length

f=3.9~46.8mm

HFOV

72.5°~6.3°

PTZ

Pan

-170° ~ +170°; 0.1° ~ 100°/s

Tilt

-30° ~ +90°; 0.1° ~ 80°/s

Preset Number

64

Image Flip

Support

General

Control Protocol

VISCA (Support daisy chain),
PELCO-P, PELCO-D

Power

DC12V; <18W

Operating Temperature

0°C ~ +40°C

Storage Temperature

-20°C ~ +60°C

Dimensions(L×W×H)

243mm×145mm×163mm

Weight

≤1.5kg

Camera

Digital Zoom

8x

Focus

Auto, Manual, One Push
Trigger, PTZ Trigger

Shutter Speed

1/60 ~ 1/10,000s

AGC

Auto, Manual

White Balance

Auto, One Push,
Manual, Auto Tracking,
Static Color
Temperature

AE Control

Auto, Manual, Shutter
Priority, Iris Priority,
Bright Priority

SNR

≥50dB

DNR

2D/3D

BLC

Support

Interface

HDMI

1 × HDMI, support
1080P60/P50/P30/P25,
1080I60/50, 720P60/P50

USB 2.0

Support MJPEG/H.264,
video output 1080P30, 720P30,
360P30

Audio Interface

1 × LINE IN

Control Interface

1 × RS-232 IN, 1 × RS-232 OUT