







# 1/1.8 Inch 4KP60 Dual Cam PTZ Camera

PVC-230

 Powerful AI	 4KP60	 30x Optical Zoom	 Dual Cam	 12G-SDI (Optional)	 NDI HX3/SRT/ Dante AV-H
--	--	---	---	---	---

**NDI HX3**  
**Dante AV-H\***  
**SRT**



## Features

- Integrated dual-lens 4K P60 design for simultaneous close-up and full-view video output;
- 1/1.8-inch 30x optical zoom lens for large scenes;
- Distortion-free panoramic lens for wide-angle images;
- Broadcast frame rates of 59.94/29.97;
- AI Face AF for fast, accurate focus;
- 3G-SDI, HDMI 2.0, Gigabit POE, and USB 3.0 video outputs;
- Front and rear dual Tally lights;
- External SD card support for one-touch recording;
- Compatible with NDI HX3, Dante AV-H, and SRT protocols;
- WEB UI for remote configuration;
- Advanced AI algorithms for stable tracking and posture recognition;
- Optional 12G-SDI, optional Full NDI, HDBaseT or SDVoE;
- Free D protocol for virtual studio setups.

## Technical Data

### Tracking Camera

**Image Sensor**  
1/1.8" CMOS, 8.46MP, up to 4KP60

**Optical Zoom**  
30x

**Digital Zoom**  
16x

**Field of View**  
HFOV: 59° ~ 2°

**Len**  
f=6.9mm ~ 215mm, F1.3 ~ F4.6

### PTZ

**Pan**  
-170° ~ +170°, 0.05° ~ 120°/s

**Tilt**  
-30° ~ +90°, 0.05° ~ 90°/s

**Preset Number**  
256

### Interface

**SDI**  
1 x 3G-SDI with audio output; up to 1080P60/P59.94/P50;  
1080i60/i59.94/i50;  
1 x 12G-SDI(Optional); up to 4KP60/P59.94/P50;  
1080i60/i59.94/i50;

**USB**  
1 x USB 3.0 Type-A (compatible with HOST), UAC and UVC 1.1, RGB 420; UVC video formats supported: H.264/H.265/MJPEG: up to 4KP60; YUY2/NV12: up to 1080P30;

### Full View Camera

**Image Sensor**  
1/1.8" CMOS, 8.46MP, max 4KP60

**Lens**  
f=4.4mm; F2.0

**HFOV**  
85°

### Image

**Focus**  
CDAF, Face AF

**Image Mode**  
One-click switching between multiple image modes

**Wide Dynamic Range**  
Dynamic Range: 0/1/2/3/4/5

**Metering Mode**  
Top, Bottom, Center, Average, Left, Right

### HDMI

1 x HDMI 2.0, with audio output, YUV/RGB 444 (8bit), YUV 422 (10bit), YUV 420 (8bit), up to 4KP60/P59.94/P50; 1080i60/i59.94/i50;

### Network

1 x RJ45, 100M/1000M adaptive Ethernet port, standard POE, with audio output AAC/G.711  
Video formats: H.264/H.265/MJPEG; up to 4KP60; Network protocols supported: RTSP/RTMP/RTMPS/Visca Over IP/ONVIF/SRT/NDI HX2/NDI HX3/Dante AV-H; Dual output for main and sub streams; WEB UI, CGI, HTTP

### General

**Power**  
DC12V, 5A

**Indicator Light**  
Power light, status light, dual Tally lights

**Installation Method**  
Upright, inverted (panoramic lens adjustable ±20°)

**Remote Control Range**  
15m, dual infrared in front and rear of camera

**Dimensions(L×W×H)**  
239mm\*208mm\*291mm

### Interface

**One of Three Options**  
Optional Full NDI, HDBaseT or SDVoE;  
Full NDI, with audio output and POE++;  
SDVoE, with audio output and POE++;  
HD-BaseT, with audio output and POE++

**Audio Interface**  
2 x Audio-Input XLR Connectors, with Phantom Power; Supports ACC/UAC; Sample Rates Supported: 16k, 32k, 48k

**Reset Button**  
Restore Factory Settings

**Control Interface**  
1 RS-232/422 Port

**Security Lock Slot**  
1 x Kensington Lock

**Memory Card**  
1 x external Micro SD slot, with a maximum storage 2TB.