

## 4KP30 PTZ Camera



4KP30



20/12x Optical Zoom



Rich Interfaces



AMC-G421S/G420B/G431S/G431B

AMC-G420S/G430S PTZ Camera is equipped with 4K CMOS sensor and UHD lens, max lossless optical zoom up to 20X, suitable for long distance shot for UHD video giving super clarity, color and details. The built-in PTZ system features high precision, and smooth movement, easy to capture objects. The camera provides rich interfaces such as 3G-SDI, HDBaseT(Optional), USB, HDMI and RJ45 etc., flexible to connect various systems, suitable for applications such as video conference, education etc.



### 4KP30, UHD Video Output

The camera is equipped with a 4K UHD CMOS sensor with 8.46MP pixels, capable of outputting rich color depth and clear, detailed 4KP30 UHD images.



### Max 20x Optical Zoom

The camera features a high-quality 4K lens with lossless optical zoom up to 20X, making it well-suited for large-scale and long-distance shooting.



### Rich Interfaces

Supports 3G-SDI, HDBaseT(Optional), USB, HDMI, and network HD output, offering a variety of interfaces for different applications.



### 256 Preset Number

The camera supports up to 256 preset positions. During operation, users can quickly call the preset positions with just a click, providing easy and quick access.



### High-Precision Pan-Tilt Unit

The camera is equipped with a high-precision PTZ (Pan-Tilt-Zoom) system, allowing the camera to smoothly rotate horizontally up to 340 degrees and vertically up to 120 degrees with precise positioning.



## Technical Data

Model	AMC-G421S/G420B		AMC-G431S/G431B
Camera			
Image Sensor	1/2.8" CMOS, 8.46MP		
Lens	20x optical zoom, 16x digital zoom; f=4.7mm ~ 94mm; F1.6 ~ F3.5; HFOV: 59.5° ~ 2.9°	12x optical zoom, 16x digital zoom; f=3.9mm ~ 46.8mm; F1.6 ~ F2.8; HFOV: 72.5° ~ 6.3°	
Focusing System	Auto, Manual, One Push Trigger, PTZ Trigger		
AGC	Auto, Manual		
White Balance	Auto, Manual, Auto Tracking, One Push, Static Color Temperature		
Exposure	Auto, Manual, Shutter Priority, Iris Priority		
BLC	Support		
SNR	≥50dB		
Anti-Flicker	Support		
PTZ			
Pan	-170° ~ +170°, 0.1° ~ 120°/s		
Tilt	-30° ~ +90°, 0.1° ~ 90°/s		
Preset Number	256		
Image Filp	Support		
Interface			
HDMI	1 channel HDMI1.4; 4KP30/P25, 1080P60/P50/P30/P25, 720P60/P50/P30/P25		
Network	1 channel RJ-45, 10M/100M, POE supported.; 1.Up to 4KP30 video output 2.Image Compression: H.264/H.265 3.Protocol: ONVIF/RTSP/RTMP/RTMPS/SRT/TCP/UDP/RTMPS/GB28181 4.Audio Compression: AAC 5.Support dual streams.		
USB 2.0	1 channel USB3.0 1.Support UVC1.1; 2.UVC Support: YUY2/IV12: 1080P30/P25, 720P30/P25, 480P30/P25, 360P30/P25; H.264/H.265/MJPEG: 4KP30/P25, 1080P60/P50/P30/P25, 720P60/P50/P30/P25, 360P30/P25 3.UAC Audio Format: PCM		
3G-SDI	1080P60/P50/P30/P25; 720P60/P50/P30/P25		
HDBaseT(Optional)	4KP30/P25, 1080P60/P50/P30/P25, 720P60/P50; Supports power supply and control, and the transmission distance can reach up to 70 meters.		
Audio	1 channel LINE IN, 3.5mm		
Control Interface	1 channel RS-232 IN, 1 channel RS-232 OUT		
General			
Control Protocol	VISCA, PELCO-P, PELCO-D		
Power	DC12V, <15W		
Operating Temperature	0℃ ~ 40℃		
Storage Temperature	-20℃ ~ +60℃		
Dimensions (L×W×H)	211mm×137mm×170mm		
Weight	≤1.2kg		

The information contained herein is subject to change without notice. We shall not be liable for technical or editorial errors or omissions contained herein.  
(Updated on July 2nd.)

## Hangzhou Chingan Tech Co., Ltd

Add: 4F, Bldg. 4, 16# Xiyuan Yi Road, Hangzhou, China  
[www.ismart-video.com/sales@ismart-video.com](http://www.ismart-video.com/sales@ismart-video.com)



Website



Linkedin



YouTube