


# 4K PTZ Camera

## AMC-G403



- 1 USB 3.0
- 2 LINE IN
- 3 LAN
- 4 DC 12V

## Features

- 1/2.8" CMOS, 8.46MP;
- 3x lossless zoom @ 4K video output, 6x lossless zoom @ 1080P video output, 9x lossless zoom @ 720P video output, with a maximum HFOV up to 81.4°;
- USB 3.0 with max 4K video output;
- Standard UVC/UAC protocol;
- H.265/H.264 video compression;
- Network and USB 3.0 outputs;
- Dual stream.

## Technical Data

### Camera

#### Image Sensor

1/2.8" CMOS, 8.46MP

#### Optical Zoom

3x

#### Focal Length

f=3.3mm ~ 9.7mm

#### Iris

F2 ~ F3.7

#### HFOV

81.4° ~ 31.3°

#### Digital Zoom

5x

#### Focus System

Auto, Manual, PTZ Trigger, One Push Trigger

#### Shutter speed

1/50 ~ 1/10,000s

#### Min. Illumination

1.0Lux (Color)

#### AGC

Auto, Manual

#### White Balance

Auto, Manual, Auto Tracking, One Push, Specified Color Temperature

#### BLC

Support

#### Wide Dynamic

Support

#### Exposure

Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority

#### SNR

≥50dB

### General

#### Power

DC12V; <12W

#### Operating Temperature

0°C ~ +40°C

#### Storage Temperature

-20°C ~ +60°C

#### Dimensions (L×W×H)

176mm×137mm×171mm

#### Weight

≤1.2kg

### PTZ

#### Pan

-170°~+170°; 0.1°~120°/s

#### Tilt

-30°~+90°; 0.1° ~ 90°/s

#### Image Filp

Support

#### Preset Number

256

### Interface

#### Network

1 × RJ45: 1×10M/100M

1. Image Compression: H.264/H.265: 4KP30/P25, 1080P60/P50/P30/P25, 720P60/P50/P30/P25

2. Protocol: ONVIF/RTSP/RTMP/TCP/UDP /RTMPS/GB28181

3. Audio Compression: AAC/G.711

4. Multi-Streams

#### USB 3.0

1. Support UVC1.1

2. UVC Support: H.264/H.265/MJPEG: 4KP30/P25, 1080P30/P25, 720P30/P25

YUY2/NV12: 1080P30/P25, 720P30/P25

3. UAC Audio Format PCM

#### Audio

1 × LINE IN, 3.5mm